Worksafe U-Damp

Innovative and unique, soft, ovalshaped foam earplugs guarantee a comfortable fit.

- The band is ergonomically shaped and its stability limits contact with clothing and resulting sound transmission
- Weighing only 8 g
- Ideal for short-term use, such as when passing through noisy premises or for visitors
- Less environmental impact when the plugs can be replaced




Item no.DescriptionColor40210864U-Damp banded ear plugBlack40210865U-Damp replacement plugs 5 pair/boxYellow





U-Damp







European Standard EN 352-2		SNR: 24 c		
Attenuation data	H: 27 dB	M: 19 dB	L: 18 dB	

1. Frequency Hz	63	125	250	500	1000	2000	4000	8000
2. Mean Attenuation dB	23.7	22.0	21.6	19.0	23.8	31.9	39.6	39.6
3. Standard Deviation dB	4.0	2.9	4.7	4.3	3.6	4.0	2.7	3.7
4. Assumed Protection dB (APV)	19.7	19.1	16.9	14.7	20.2	27.9	36.9	35.9

Sizes range: Sma**ll**/Medium/Large Größenbereiche: Klein/Mittel/Groß Taille: Petite/Moyenne/Grande Acc. to EN 352-2:1993

- 1. Frequenz Hz / Fréquence Hz
- 2. Mittlere Dämmung dB / Atténuation moyenne dB
- 3. Standardabweichung dB / Ecart type dB
- 4. Angenommene Schutzwirkung dB / Protection effective en dB

EN 352

FITTING INSTRUCTIONS

Ensure correct seal and fit by carefully follow the instructions below:

1. Hold the band under your chin, with earplugs pointing forward.

Fit plugs over ear canal entries with band under the chin.

2. Adjust the fit by pushing the band and plug gently with a slight rocking and twisting, at the same time as you pull the outer ear upwards/backwards with your free hand. Adjust opposite side accordingly.

- These banded earplugs are designed for wearing mode "under-the-chin" only.
- Band shall be worn with earplugs pointing forward only.
- Do not roll/compress plugs before fitting.

Made in Sweden

