

## HS CODE

6307909899

## CARTON SIZE / PCS.






60 x 40 x 24 cm / 5

AET (UE) N°2777/13781-01/E01-01

**Satra Technology Europe Ltd., N° 2777,**  
 Bracetown Business Park, Clonee,  
 Dublin, D15YN2P, Ireland

## MODULE D FI14/14003.02

**SGS Fimko Oy, N°0598**  
 Takomotie 8,  
 00380 HELSINKI, Finland

REF.	FA 60 007 00
CE	PPE regulation (EU) 2016/425 Annex II using EN 795:2012, TS 16415:2013
	x2
MAT.	 30 mm PES
R (kN) / MBS (kN)	19 kN / 23 kN
MAT. 	
LG. / f MIN. → MAX.	2.0 m → 20.0 m / 0.8 m → 3.2 m
	3.43 KG



**R (kN) / MBS (kN)**

**Nombre d'utilisateurs**  
Number of users  
**Cantidad de usuarios**  
Quantità di utilizzatori  
**Anzahl der Benutzer**

**Résistance statique (en kN) / Résistance à la rupture**  
Static strength / Minimum Breaking Strength  
**Resistencia estática (en kN) / Resistencia a la ruptura (en kN)**  
Resistenza statica (in kN) / Resistenza alla rottura (in kN)  
**Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)**



**LG. / f MIN. MAX.**

**Matière connecteur / tendeur**  
Material of connector / tensioner  
**Material del conector / tensor**  
Materia del connetore / tenditore  
**Material Verbinder / Spanner**

**Longueur mini → maxi / Flèche mini → maxi**  
Min. → Max. length / Min. → Max. deflection  
**Longitud mínima → máxima / Flecha mínima → máxima**  
Lunghezza min. → max. / Flessione min. → max.  
**Länge min. → max. / Dirchhang min. → max.**