TouchNTuff® 92-500 92-600 92-605



Single Use



Splash



Proven splash resistance against hazardous chemicals

DESCRIPTION

- Further testing of the TouchNTuff® by a certified body on an even wider range of chemicals confirms that it resists a greater variety of industrial chemicals for longer periods than any other nitrile disposable gloves. Manufactured from nitrile, TouchNTuff® offers up to four times the puncture resistance of
- comparable natural-latex gloves, and three times the resistance of similar neoprene gloves. It contains no natural rubber proteins, which means no risk of Type I allergies for the
- wearer. Primary skin irritation studies and Insult Patch tests have also shown on evidence of risk from irritation or allergic contact dermatitis. With a unique "Thin Nitrile Technology" formulation, this glove offers easy donning and
- Strong grip in wet or dry conditions. The glove is highly versatile and suitable for many different uses.
- •


PRODUCT DETAILS

Coating material	Nitrile
Grip design	92-500,92-605: Textured fingertips 92-600: Smooth
Cuff style	Rolled beaded
Thickness (mm)	0.12
Extra features	92-500,92-605: Antistatic Silicone Free 92-600: Antistatic Silicone Free Vending
Colour	Green
AQL	1.5
EN Sizes	6.5 - 7,7.5 - 8,8.5 - 9,9.5 - 10
Length (mm)	92-500,92-600: 240 92-605: 300
Packaging	100 gloves in a box; 10 boxes in a carton


IDEAL APPLICATIONS

- Chemical handling
- Electronics •
- Glass manufacturing
- . Handling of cytostatics
- Intricate parts handling
- Laboratory analysis
- Light assembly of oil-coated pieces
- Light assembly tasks
- Paint and spray shops
- Pharmaceuticals
- Printing industry

PRIMARY INDUSTRIES



STANDARDS AND CERTIFICATIONS





Print date 28-06-2019

Ansell Healthcare Europe N.V. (European Head Office) Riverside Business Park, Block J

Boulevard International 55, 1070 Brussels, Belgium Tel. +32 (0) 2 528 74 00 • Fax +32 (0) 2 528 74 01 • Fax Customer Service +32 (0) 2 528 74 03 http://www.ansell.eu • E-mail info@ansell.eu

